MATERIAL SAFETY DATA SHEET

Z.P.W. WOOD PRESERVATIVE

HMIS CODES: H F R P **PRODUCT NAME:** Z.P.W. WOOD PRESERVATIVE

PROCUCT CODE: 0930-0933 1*1 0 B

JASCO Chemical Corp. MANUFACTURER'S NAME :

1008 N. Fuller St. **ADDRESS**

Santa Ana, CA. 92701

EMERGENCY PHONE 800-424-9300 DATE PRINTED : 6/01 INFORMATION PHONE : (714)547-6951 NAME OF PREPARER : RE

======= SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ===========

VAPOR PRESSURE WEIGHT

Page:

REPORTABLE COMPONENTS CAS NUMBER mm Hg @ TEMP

ZINC NAPHTHENATE SOLUTION; M-GARD W152 OSHA PEL: UNKNOWN, ACGIH TLV: 5 MG/M3, OTHER: 10 MG/M3

No toxic chemical (s) subject to the reporting requirements of section 313 of Title III of 40 CFR 372 are present. *** No information available

BOILING RANGE: 110 DEG. F **SPECIFIC GRAVITY (H2O=1):** 1.00 VAPOR DENSITY: HEAVIER THAN AIR **EVAPORATION RATE:** UNKNOWN

COATING V.O.C.: $340.8 \, g/L$

SOLUBILITY IN WATER: COMPLETE

APPEARANCE AND ODOR: WHITE LIQUID; SLIGHT SWEET ODOR.

========= SECTION IV - FIRE AND EXPLOSION HAZARD DATA ==========================

FLASH POINT: >200 DEG. F METHOD USED: N/D FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A **UPPER:** N/A

EXTINGUISHING MEDIA: ALCOHOL FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

FIREFIGHTERS SHOULD WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING WHEN FIGHTING FIRES.

UNUSUAL FIRE AND EXPLOSION HAZARDS

VAPORS ARE HEAVIER THAT AIR AND MAY BE MOVED BY AIR CURRENTS TO DISTANT IGNITION SOURCES.

STABILITY: STABLE CONDITIONS TO AVOID

NONE KNOWN.

INCOMPATIBILITY (MATERIALS TO AVOID)

CO, CO2, VARIOUS HYDROCARBONS.

MATERIAL SAFETY DATA SHEET

Z.P.W. WOOD PRESERVATIVE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

NONE KNOWN.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

MAY CAUSE DIZZINESS, FATIGUE, HEADACHE.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN AND EYE IRRITANT.

SKIN ABSORPATION HEALTH RISKS AND SYMPTONS OF EXPOSURE

REDNESS, DEFATTING, DERMATITIS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

MAY CAUSE GASTROINTESTINAL TRACT IRRITATION, NAUSEA, VOMITING AND DIARRHEA.

HEALTH HAZARDS (ACUTE AND CHRONIC)

HARMFUL OR FATA IF SWALLOWED. NAUSEA, VOMITING, DIARRHEA, DIZZINESS, FATIGUE.

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

THIS PRODUCT IS NOT LISTED IN THE NTP, IARC OR OSHA LISTS FOR CARCINOGENICITY.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

SOME SKIN CONDITIONS MAY BE AGGRAVATED.

EMERGENCY AND FIRST AID PROCEDURES

SKIN: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. SEEK MEDICAL ATTENTION IF IRRITATION PERSISTS. INGESTION: DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL ATTENTION.

======= SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ==============

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

CONTAIN AND ABSORB WITH INERT MATERIAL.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP CONTAINER CLOSED WHEN NOT IN USE.

OTHER PRECAUTIONS

DO NOT STORE NEAR HEAT OR OPEN FLAME.

Page: 2

MATERIAL SAFETY DATA SHEET

REPIRATORY PROTECTION NIOSH-APPROVED RESPIRATOR IF TLV IS EXCEEDED.

Page: 3

VENTILATION

LOCAL EXHAUST IS PREFERRABLE AND MECHANICAL EXHAUST IS ACCEPTABLE.

PROTECTIVE GLOVES

SOLVENT RESISTANT SUCH AS NEOPRENE.

Z.P.W. WOOD PRESERVATIVE

EYE PROTECTION

SAFETY GLASSES/GOGGLES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

SAFETY SHOWER/EYEWASH.

WORK/HYGIENIC PRACTICES

DO NOT EAT, DRINK OR SMOKE AROUND PRODUCT. WASH HANDS AFTER USE.

THIS INFORMATION IS TO THE BEST OF OUR KNOWLEDGE AND BELIEF ACCURATE AS OF THE DATE COMPILED. HOWEVER, NO REPRESENTATION OR GUARANTEE IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS.